

BIO 1000

FUEL STABILISER AGAINST BACTERIA AND FUNGI

DESCRIPTION

BIO 1000 is a broad-spectrum fuel stabilizer for the prevention and control of the growth of bacteria and fungi on hydrocarbon-based fuels, such as diesel, heating oil, kerosene and fuel oil.

APPLICATION & USE

BIO 1000 is used not only to suppress but also to prevent the growth of bacteria and fungi in the oil as well as any phenomena of bio-deposits. As the addition of biodiesel in diesel is mandatory, bio-deposits are favored. Biodiesel disperses moisture, leading to the growth of microorganisms, which results in the oil becoming unstable. The main problems that occur are clogged filters, rusty tanks, turbidity of fuel and deposit build-up. By using **BIO 1000** all the above problems will be drastically addressed.

The dosage range of **BIO 1000** is 1 liter of additive for 1,000 liters of fuel for suppression and 1 liter of **BIO 1000** for 2,000-3000 liters of fuel for prevention of bacteria/fungi growth and oxidation of fuel. The exact dosage depends on the fuel quality and the extent of the problem (in case of suppression). Add **BIO 1000** in the tank before refueling. Finally, you can apply **BIO 1000** proactively at least once or twice a month depending on the frequency of refueling.

PACKAGING

BIO 1000 is available in 1 ltr pails with a dose meter.

- ✓ High efficiency fuel stabilizer against bacteria and fungi specific for oils
- ✓ Solves clogging problems created from the presence of moisture or biodiesel in oil
- ✓ Ability to apply the product for immediate suppression and also for protection & maintenance

PRODUCT CODE: FA112-70