

BIO 6000.53

CONCENTRATED FUEL STABILISER AGAINST BACTERIA AND FUNGI

DESCRIPTION

BIO 6000.53 is a concentrated broad-spectrum fuel stabilizer, specially designed to prevent and control the growth of bacteria and fungi on hydrocarbon-based fuels, such as diesel, heating oil, kerosene and fuel oil.

APPLICATION & USE

BIO 6000.53 has dual action as it can be applied not only to suppress but also to prevent the growth of bacteria and fungi in the oil as well as any phenomena of bio-deposits. Bio-deposits have become a very common problem of diesel due to the mandatory addition of biodiesel, which on the one hand favors the dispersion of moisture and the easy growth of microorganisms and on the other hand makes the oil relatively unstable. This leads to clogged filters, rusty tanks, turbidity of fuel and deposit build-up. Use **BIO 6000.53** to drastically address all the above problems.

The dosage range of **BIO 6000.53** is 1 liter of additive for 8,000-10,000 liters of fuel for suppression and 1 liter of **BIO 6000.53** for 20,000 liters of fuel for prevention of bacteria/fungi growth and oxidation of fuel. The exact dosage depends on the fuel quality and the extent of the problem (in case of suppression). Add **BIO 6000.53** in the tank before refueling. Finally, you can apply **BIO 6000.53** proactively at least once or twice a month depending on the frequency of refueling.

PACKAGING

BIO 6000.53 is available in 1 ltr pails (box of 16), 25 ltr pails and 208 ltr drums.

- ✓ High efficiency fuel stabilizer against bacteria and fungi specific for oils
- ✓ Solves clogging problems created from the presence of moisture or biodiesel in oil
- ✓ Ability to apply the product for immediate suppression and also for protection & maintenance

PRODUCT CODE: FA112-70